

Emacs Req NG Reference Card

(for reqng-1.3.5 locally patched at kom.auc.dk)

Emacs Request Interface

All commands are located in the `/pack/reqng` directory
Angle brackets indicate needed arguments for commands

View Commands

SPC View or scroll current request
DEL Scroll the displayed request backwards
n View next request
p View the previous request
. Reset the display and reread
x Expand to show the mail headers

Assignment Commands

r Resolve current request
k Kill current request
t Take current request
M-t Untake current request
s Stall current request
M-s Unstall current request
S Steal current request
o Explicitly reopen a resolved request
g Give this request to someone else (prompts)
P Set a request's priority (prompts)
M Merge this request with another (prompts)
R Change requesting user of current request

Reply and Comment Commands

c Compose a comment on current request
m Mail message to requester on current request
l Start process to monitor request log

Update Commands

n Update request queue display
U Update, applying `reqg-default-filter-args`
C-c U Update, prompting for filter arguments

Quit

q Clean up and quit.

Mail Buffer Commands

When commenting on a request, C-c Cs records the comment.
When sending mail, all the normal sendmail bindings are active. Additionally:

C-c C-r Marks request resolved
C-c C-g Prompts to give request to someone else
C-c C-l Marks request stalled
C-c C-p Prompts to prioritize request
C-c C-t Marks request taken
C-c C-u Changes requester
C-c C-y Yanks text of the request into message
C-c C-v Views text of request

When in the log buffer, SPC displays the request related to a log entry, and q kills the process and deletes its buffer.

Req NG Variables

Variables controlling this mode:

`reqg-resize-window` If true, resize queue window when displaying requests.
`reqg-default-filter-args` arguments to the queue display" command which should filter the output in some useful fashion. The contents of this variable should be a string of the arguments to pass.
`reqg-display-filter-helper` if true, display the legal arguments for the queue command when prompting for arguments.
`reqg-hide-headers` If true, hide the first set of headers on a request when displaying the request, making it much more readable. x unhides the headers.
`reqg-annoy-me` If true, display chunks of the request log in the message area as emacs finds out about them. See the variable documentation to find out why this is generally Not A Good Thing.
`request-queue-mode-hook` Entering this mode calls value of hook variable `request-queue-mode-hook`.

Copyright © 2001 Flemming Kjær Jensen
v1.0 for Emacs Req NG version 1.3.5, January 2001
designed by Flemming Kjær Jensen

Permission is granted to make and distribute copies of this card provided the copyright notice and this permission notice are preserved on all copies.