

## Technical Specification | Audience 52

Sensitivity (2.83 V/1 m):	86 dB
Recommended Amp. Power: Small size rooms:	>25 watts
Medium size rooms:	>65 watts
Large size rooms:	-- watts
IEC Long Term Power Handling:	150 watts
Impedance, Nominal:	4 ohms
Impedance, (20-200 Hz):	3.7 - 11 ohms
Impedance, (200-20 kHz):	3.7 - 9.6 ohms
Impedance, Phase Shift (20-200 Hz):	-32° - +31°
Impedance, Phase Shift (200-20 kHz):	-11° - +29°
Impedance, HF (200 kHz):	5.8 ohms
Frequency Response (+/- 3 dB):	52 Hz - 24 kHz
Resonance Frequency:	47 Hz
Internal Cabinet Volume:	10 litres
Bass Principle:	Bass reflex
Weight:	6.9 kg
Dimensions (W x H x L):	204 x 330 x 256 mm
Crossover:	2 way. The crossover is impedance corrected
Crossover Frequencies:	2700 Hz
Crossover Slope:	Woofer 6 dB/oct; Tweeter 12 dB/oct
Connection:	CE compliant insulated gold binding posts
Recommended Placing:	Stand

Remarks:	Tweeter: 28 mm soft dome. Magnetic fluid. Pure aluminium wire voice coil. Rear chamber.
	Woofer: 17 cm polypropylene cone. 75 mm pure aluminium wire voice coil.
	Cabinet: Front baffle 19 mm MDF. Port plugs included. Bitumen damped enclosure.

**DYNAUDIO International GmbH**

Ohepark 2  
21224 Rosengarten  
Germany  
Phone +49 (0)4108 - 4180 - 0  
Fax +49 (0)4108 - 4180 - 10  
E-Mail [info@dynaudio.de](mailto:info@dynaudio.de)